

ERRATUM

Erratum: “Adaptive Trellis Using Interim Maximum-Likelihood Detector Output for a Holographic Storage System”

To cite this article: Gukhui Kim *et al* 2016 *Jpn. J. Appl. Phys.* **55** 119203

View the [article online](#) for updates and enhancements.

You may also like

- [Adaptive Equalization Using Expanded Maximum-Likelihood Detector Output for Optical Recording Systems](#)
Joohyun Lee and Jaejin Lee
- [Model of a non-transferred arc cascaded-anode plasma torch: the two-temperature formulation](#)
Rodion Zhukovskii, Christophe Chazelas, Vincent Rat et al.
- [Computational modeling of CO₂ conversion by a solar-enhanced microwave plasma reactor](#)
Rasool Elahi, Ephraim M Simasiku and Juan P Trelles



Erratum: “Adaptive Trellis Using Interim Maximum-Likelihood Detector Output for a Holographic Storage System” [Jpn. J. Appl. Phys. 50, 09ME06 (2011)]

Gukhui Kim, Jinyoung Kim, and Jaejin Lee*

School of Electronic Engineering, Soongsil University, Seoul 156-743, Korea

*E-mail: zlee@ssu.ac.kr

Received September 13, 2016; accepted September 13, 2016; published online October 5, 2016

Acknowledgment should be added in this article as follows.

“This work was supported by the Basic Research Laboratory (BRL) through an NRF grant funded by the MSIP (No. 20110020262).”