PAPER • OPEN ACCESS

LDA Extension via Oblique Projection

To cite this article: B J Yang et al 2018 J. Phys.: Conf. Ser. 1060 012049

View the article online for updates and enhancements.

You may also like

- <u>Defect levels in d-electron containing</u> systems: Comparative study of CdTe using LDA and LDA + U Yuan Yin, Yu Wang, Guangde Chen et al.
- DFT-1/2 and shell DFT-1/2 methods: electronic structure calculation for semiconductors at LDA complexity Ge-Qi Mao, Zhao-Yi Yan, Kan-Hao Xue et al.
- <u>High-density amorphous ice: nucleation of</u> <u>nanosized low-density amorphous ice</u> Christina M Tonauer, Markus Seidl-Nigsch and Thomas Loerting





DISCOVER how sustainability intersects with electrochemistry & solid state science research



This content was downloaded from IP address 13.59.154.190 on 15/05/2024 at 14:55

IOP Publishing

LDA Extension via Oblique Projection

B J Yang¹, W G Shang² and Y J Wu^{2,*}

¹ School of Mathematic Sciences, Guizhou Normal University, Guiyang, P.R. China
² School of Information Engineering, Guangdong Medical University, Dongguan, P.R. China

*E-mail: wuyingjiang@163.com

Abstract. The classical linear discriminant analysis (LDA) was previously modified by orthogonal projection into null space LDA (N_LDA) and direct LDA (D_LDA) for solving small sample size (SSS) problem. In this paper, the author proposes an extension of LDA by oblique projection, wherein N_LDA and D_LDA are included as special cases, to reduce discriminative information loss resulted from single N_LDA or D_LDA. The effectiveness of the proposed algorithm is tested by image forensics and face recognition.

1. Introduction

Linear discriminant analysis (LDA) is one of the most popular means in pattern recognition [1]. The objective of LDA is to find a projection W that maximizes the ratio of the between-class scatter matrix, S_b , against the within-class scatter matrix, S_w , i.e., via the following Fisher criterion:

$$J(W_{opt}) = \arg \max_{W} \frac{|WS_{b}W^{T}|}{|WS_{w}W^{T}|}.$$
(1)

One of the major drawbacks of LDA is the so-called small sample size (SSS) problem encountered in many practical applications involving high dimensional data [1]. Many techniques have been proposed to solve this problem, and Ref. [2] may be consulted in detail. Among them, the most notable approaches are null space LDA (N_LDA) and direct LDA (D_LDA) [2, 3], which are based on the following modified Fisher criterion [4]:

$$WS_{w}W^{T} = 0 \quad and \quad WS_{b}W^{T} \neq 0.$$
⁽²⁾

Since N_LDA and D_LDA are based on orthogonal projection, and generally the two conditions in equation (2) cannot be simultaneously satisfied, the processes are usually fulfilled in two steps: in N_LDA the null space of S_w is found first and then that of S_b is discarded, while in D_LDA the reverse order is taken. In this manner, much discriminated information may be lost.

In this paper, an extension of LDA is proposed by oblique projection, and it is called OP_LDA, for reduction of possible loss of discriminative information in N_LDA or D_LDA. Experimental results on image forensics and face recognition show satisfactory performance of the proposed method.

The rest of this paper is organized as follows. An overview of N_LDA and D_LDA is briefly introduced in Section 2. Section 3 describes OP_LDA and discusses the relationship among N_LDA, D_LDA and OP_LDA. In Section 4, we evaluate the performance of OP_LDA and compare its

performance with LDA, N_LDA, D_LDA, and 2-dimensional LDA (2D_LDA) [5]. Finally, conclusions are given in Section 5.

2. N_LDA and D_LDA

2.1. N_LDA

In N_LNA, the discriminative information can be found in the null space of Sw by two steps [2]: Step 1: Find the null space of S_w , Null(S_w).

Step 2: Let $S_b' = P_{\text{Null}(Sw)}(S_b)$, and then

$$W_1 = P_{\operatorname{Col}(S_h')},\tag{3}$$

where $P_{\text{Null}(S_w)}(S_b)$ is a matrix obtained by orthogonal projecting the column vectors of S_b onto Null(S_w), $\text{Col}(S_b')$ is the column space of S_b' , $P_{\text{Col}(Sb')}$ is an orthogonal projection operator onto $\text{Col}(S_b')$.

Figure 1 depicts a simple example of this algorithm, where v is an arbitrary vector in the input space, and v' is a new vector obtained from v by N_LDA.



Figure 1. A simple example of N_LDA.

2.2. D_LDA

In D_LNA, the discriminative information can be found in the column space of S_b by two steps [3]: Step 1: Find the column space of S_b .

Step 2: Let $S_w' = P_{\text{Col}(Sb)}(S_w)$, and then

$$W_2 = P_{\text{Null}_{Col(S_k)}(S_w)},\tag{4}$$

where $P_{\text{Col}(Sb)}(S_w)$ is a matrix obtained by orthogonal projecting the column vectors of S_w onto $\text{Col}(S_b)$, $\text{Null}_{|\text{Col}(Sb)}(S_w')$ is the null space of S_w' in $\text{Col}(S_b)$, $P_{\text{Null}_{|\text{Col}(Sb)}(S_w')}$ is an orthogonal projection operator onto $\text{Null}_{|\text{Col}(Sb)}(S_w')$.

Since rank(S_b), the rank of matrix S_b , is usually smaller than rank(S_w), and in this case $Col(S_w')=Col(S_b)$ and $Null|_{Col(S_b)}(S_w')=\{0\}$, the solution of D_LDA is given by

$$W_2 = P_{\operatorname{Col}(S_h)}.$$
(5)

Figure 2 depicts a simple example of this algorithm, where v is an arbitrary vector in the input space, and v' is a new vector obtained from v by D_LDA.



Figure 2. A simple example of D_LDA.

3. Proposed method

3.1. OP_LDA

We present a new LDA algorithm based on oblique projection, named OP_LDA. The objective of OP_LDA is to find a projection operator W that satisfies equation (6), which also is special circumstance of equation (2).

$$WS_w = 0 \quad and \quad WS_b \neq 0.$$
 (6)

The key idea of our algorithm is that W is an oblique projection operator, whereas the traditional methods take it as orthogonal projection. A particular solution of equation (6) is given by

$$W_3 = P_{\operatorname{Col}(S_b)|\operatorname{Col}(S_w)},\tag{7}$$

where $P_{\text{Col}(Sb)|\text{Col}(Sw)}$ is an oblique projection operator onto $\text{Col}(S_b)$ along $\text{Col}(S_w)$, and W_3 can be obtained from $\text{Col}(S_w)$ and $\text{Col}(S_b)$, Ref. [6] may be consulted in detail.

Figure 3 depicts a simple example of this algorithm, where v is an arbitrary vector in the input space, and v' is a new vector obtained from v by OP_LDA.



Figure 3. A simple example of OP_LDA.

3.2. Discussion

As shown in Figure 1, Figure 2 and Figure 3, there are three means to obtain v': a. discarding the component of $Col(S_w)$, b. keeping that of $Col(S_b)$, and c. discarding that of $Col(S_w)$ and keeping that of $Col(S_b)$ simultaneously. So it is clear that OP_LDA including N_LDA and D_LDA as special cases when $Col(S_w)$ and $Col(S_b)$ are orthogonal.

The traditional methods emphasize S_w or S_b respectively, and our method emphasizes S_w and S_b simultaneously. For discarding Col(S_w) in N_LDA, S_b is converted into S_b' by projecting onto Null(S_w). Since there are differences between S_b and S_b' , discriminated information may be lost by adopting S_b' . The similar drawback may appear in D_LDA. Therefore discriminative information loss in N_LDA or D_LDA may be reduced by adopting S_w and S_b directly in OP_LDA.

3.3. Analysis

The following condition needs to be satisfied in using $P_{\text{Col}(Sb)|\text{Col}(Sw)}$: the direct sum of $\text{Col}(S_b)$ and $\text{Col}(S_w)$ must be equal to the input space [6]. Since the direct sum is the sum of two disjoint spaces, it includes two meanings: the sum of $\text{Col}(S_b)$ and $\text{Col}(S_w)$ must be equal to the input space, and $\text{Col}(S_b)$ and $\text{Col}(S_w)$ must be disjoint, i.e., $\text{Col}(S_w)\cap\text{Col}(S_b)=\{0\}$.

Since the sum of $\operatorname{Col}(S_b)$ and $\operatorname{Col}(S_w)$ is a subspace of the input space, $P_{\operatorname{Col}(Sb)|\operatorname{Col}(Sw)}$ is invalid for vectors which do not belong to the sum space. Therefore we project vectors in this case onto $\operatorname{Col}(S_t)$ first, where S_t denotes the total scatter matrix. Since $\operatorname{Null}(S_w) \cap \operatorname{Null}(S_b) = \operatorname{Null}(S_t)$ has been proven in Ref. [7], and S_w , S_b and S_t are symmetric matrixes, it is clear that $\operatorname{Col}(S_t)$ is the sum of $\operatorname{Col}(S_b)$ and $\operatorname{Col}(S_w)$.

If $\operatorname{Col}(S_w) \cap \operatorname{Col}(S_b) \neq \{0\}$, $P_{\operatorname{Col}(Sb)|\operatorname{Col}(Sw)}$ does not exist. This is a more complicated problem. In this paper we consider a simple scheme as follow:

$$W_{3} = \begin{cases} P_{\operatorname{Col}(S_{b})|\operatorname{Col}(S_{w})} P_{\operatorname{Col}(S_{t})}, \operatorname{Col}(S_{w}) \mid \operatorname{Col}(S_{w}) = \{0\} \\ P_{\operatorname{Col}(S_{b})|P_{\operatorname{Col}(S_{w})}\operatorname{Null}(S_{b})} P_{\operatorname{Col}(S_{t})}, otherwise. \end{cases}$$

$$\tag{8}$$

IOP Publishing

where $P_{\text{Col}(St)}$ is a orthogonal projection operator onto $\text{Col}(S_t)$, $P_{\text{Col}(Sw)}\text{Null}(S_b)$ is a space obtained by orthogonal projecting the vectors of $\text{Null}(S_b)$ onto $\text{Col}(S_w)$, and $P_{\text{Col}(Sb)|P_{\text{Col}(Sw)}\text{Null}(S_b)}$ is an oblique projection operator onto $\text{Col}(S_b)$ along $P_{\text{Col}(Sw)}\text{Null}(S_b)$.

Figure 4 depicts a simple example of our method, where v is an arbitrary vector in the input space, and v' is a new vector obtained from v by equation (8). It is clear that we want v' to lie in $Col(S_b)$ and discard the partial components of $Col(S_w)$.



Figure 4. A simple example of proposed method for $Col(S_w) \cap Col(S_b) \neq \{0\}$.

4. Experimental results

4.1. Experimental setup

We illustrate the efficacy of the proposed method on image forensics and face recognition. As application-based development, some parameters and schemes have been empirically determined in our implementation.

For finding the null space and the column space of an arbitrary symmetric matrix, M, we perform first the singular value decomposition of M as $M=U\sum V^{T}$, and then let $Col(M)=span\{u_{1},...,u_{r}\}$ and

Null(*M*)=span{ $u_{r+1},...,u_n$ }, where $U=[u_1,...,u_r,u_{r+1},...,u_n]$, $u_1,...,u_r$ correspond to the nonzero eigenvalues, and $u_{r+1},...,u_n$ correspond to the zero eigenvalues [8].

In order to conform whether $\operatorname{Col}(S_b)$ and $\operatorname{Col}(S_w)$ are disjoint, we consider a simple scheme via the following dimensional formula [9]: if $\operatorname{rank}(S_t) = \operatorname{rank}(S_b) + \operatorname{rank}(S_w)$, then $\operatorname{Col}(S_w) \cap \operatorname{Col}(S_b) = \{0\}$, otherwise $\operatorname{Col}(S_w) \cap \operatorname{Col}(S_b) \neq \{0\}$.

To evaluate the performance of the proposed method, the training samples are randomly selected about half of the image dataset to train the classifier, and the remaining images are used in testing.

4.2. Image forensics

OP_LDA is tested by blurring detection in image forensics. The dataset and feature extraction are same as Ref. [10], wherein details can be found. The dataset consists of 183 authentic images and 183 forged images, and three types of feature vectors respectively consisted of the singular values of gray image matrix, correlation coefficients for double blurring operation, and image quality metrics are extracted and then fused for forgery detection.

In comparison, Table 1 lists the detection rates of the following four different detection schemes: feature fusion obtained respectively by LDA, N_LDA, D_LDA, and OP_LDA, respectively plus Euclidean distance (ED) classifier. In this table, "--" means that LDA is ineffective, due to the SSS problem.

Table 1. Detection rate vs. different schemes in image forensics.

Scheme	Detection rate (%)	
LDA+ED		
N_LDA+ED	86.81	
D_LDA+ED	60.55	
OP_LDA+ED	86.81	

Since image forensics is in fact a binary classification problem, and in this case $Null(S_w)$ is lost in D_LDA, D_LDA performs poor. While $Col(S_b)$ is kept in N_LDA, so N_LDA obtained the same result as OP_LDA in this experiment.

4.3. Face recognition

OP_LDA is tested by face recognition using three face datasets: YALE, ORL, and PIE, details can be found in Ref. [5]. The YALE dataset contains 165 face images of 15 persons. The image size is 100×100 . We subsample the images down to a size of 25×25 . The ORL dataset contains 400 face images of 40 persons. The image size is 92×112 . We subsample the images down to a size of 23×28 . The PIE dataset is a subset of the CMU_PIE face image dataset. It contains 6615 face images of 63 persons. The image size is 486×640 . We subsample the images down to a size of 98×128 . Table 2 lists the recognition rates of the following five different schemes: feature extraction obtained respectively by LDA, N_LDA, D_LDA, OP_LDA, and 2D_LDA, respectively plus ED classifier.

Table 2. Recognition rate vs. different schemes in face recognition.

Database Scheme	YALE	ORL	PIE
LDA+ED			
N_LDA+ED	92.93	93.6	100
D_LDA+ED	87.87	89.1	96.39
OP_LDA+ED	93.07	93.75	98.59
2D_LDA+ED	92.53	93.4	99.99

experiments.

IOP Conf. Series: Journal of Physics: Conf. Series 1060 (2018) 012049 doi:10.1088/1742-6596/1060/1/012049

IOP Publishing

The results demonstrate that our proposed method can achieve comparable performance to 2D_LDA in [5]. Compared to the prior arts in [2, 3], OP_LDA performs better than N_LDA and D_LDA in using YALE and ORL face datasets. Due to the SSS problem, LDA is ineffective in these

5. Experimental results

An extension of LDA by oblique projection for solving SSS problem is proposed in this paper. Instead of using orthogonal projection, oblique projection is adopted to reduce possible discriminative information loss in N_LDA or D_LDA, two popular modified versions of the traditional LDA. Experimental results on image forensics and face recognition showed satisfactory performance of the proposed method. OP_LDA may be converted into a nonlinear version by kernel method, which is one of our future tasks.

Acknowledgments

This work was supported in part by the Doctor Start-up Fund of Guizhou Normal University (2016)

References

- [1] Fukunaga K 1990 Introduction to Statistical Pattern Recognition 2th ed. (New York: Academic Press) chapter 10
- [2] Chen L F, Liao H Y M, Ko M T, Lin J C and Yu G J 2000 A new LDA-based face recognition system which can solve the small sample size problem *Pattern Recognition* **33(10)**, 1713–26
- [3] Yu H and Yang J 2001 A direct LDA algorithm for high-dimensional data: with application to face recognition *Pattern Recognition* **34(10)** 2067–70
- [4] Liu K, Cheng Y Q and Yang J Y 1993 Algebraic feature extraction for image recognition based on an optimal discriminant criterion *Pattern Recognition* **26(6)** 903–911
- [5] Ye J P, Janardan R and Li Q 2004 Two-dimensional linear discriminant analysis *Advances in Neural Information Processing Systems* **17** 1569–76
- [6] Liu B Y 2012 Incremental learning of oblique projection-based kernel discriminator: Theory and algorithm *Sciencepaper Online*
- [7] Yang J, Zhang D and Yang J Y 2003 A generalised K-L expansion method which can deal with small sample size and high-dimensional problems *Pattern Analysis and Applications* **6(1)** 47–54
- [8] Zhang X D 2004 Matrix Analysis and Applications (Beijing: Tsinghua University Press) pp 609–612
- [9] Li D C 1995 On Theorems of Dimensions and Bases of Subspace's Intersections *Journal of Southwest Nationalities College, Natural Science Edition* **21**(2) 224–226
- [10] Yang B J and Liu B Y 2013 Image forgery detection via multifeature classification *Journal of Pattern Recognition and Image Processing* **4**(**4**) 413–421